

3. Accessories:

- SAE-counter flanges, see sheet-no. 1652
- adapter for connection acc. to EN1092-1, see sheet-no. 1657
- adapter for ANSI-connection B16.5 CLASS 150 PSI, see sheet-no. 1658
- measure- and bleeder-connections, see sheet-no. 1650
- drain- and bleeder connection, see sheet-no. 1659

4. Spare parts:

item	qty.	designation	dimension		article-no.	
			DA 631	DA 1001		
1	2	filter element	01NL.630	01NL.1000		
2	1	change over UKK	DN 80			
3	2	O-ring	60 x 3,5		304377 (NBR)	304398 (FPM)
4	4	O-ring	135 x 4,75		326348 (NBR)	326349 (FPM)
5	2	O-ring	136,12 x 3,53		320162 (NBR)	320163 (FPM)
6	12	screw plug	NPT ½		307766	
7	2	screw plug	G ¼		305003	
8	1	clogging indicator, visual	AOR or AOC		see sheet-no. 1606	
9	1	clogging indicator, visual-electrical	OP		see sheet-no. 1628	
10	1	clogging indicator, visual-electrical	OE		see sheet-no. 1628	
11	1	clogging indicator, visual-electrical	AE		see sheet-no. 1609	
12	1	clogging sensor, electronical	VS1		see sheet-no. 1607	
13	1	clogging sensor, electronical	VS2		see sheet-no. 1608	
14	1	O-ring	15 x 1,5		315357 (NBR)	315427 (FPM)
15	1	O-ring	22 x 2		304708 (NBR)	304721 (FPM)
16	2	O-ring	14 x 2		304342 (NBR)	304722 (FPM)
17	2	screw plug	G ¼		305003	
18	1	pressure balance valve	DN 10		305000	

item 17 execution only with clogging indicator or clogging sensor

5. Description:


Pressure filters, change-over series DA 631-1001 are suitable for operating pressure up to 40 bar. Pressure peaks can be absorbed with a sufficient margin of safety. Change-over ball valve which, integrated in the middle of the housing, makes it possible to switch from the dirty filter-side to the clean filter-side without interrupting operation. The filter element consists of star-shaped, pleated filter material which is supported on the inside by a perforated core tube and is bonded to the end caps with a high-quality adhesive. The flow direction is from outside to the inside. These filters can be installed as suction filters. For cleaning (see special leaflet 21070-4 and 34448-4) the mesh element respectively to change the glass fibre element remove the cover and take out the element. Filter finer than 40 µm should use throw-away elements made of paper or Interpor fleece (glass fibre). Filter elements as fine as 5 µm_(α) are available; finer filter elements on request. Internormen Product Line filter elements are known as elements with a high intrinsic stability and an excellent filtration capability, a high dirt-retaining capacity and a long service life. Internormen Product Line filter are suitable for all petroleum based fluids, HW-emulsions, most synthetic hydraulic fluids and lubrication oils. The inspection according to TÜV, according to ASME VIII Div.1 and the major „Shipyards Classification Societies“ D.N.V.; B.V.; G.L.; L.R.S.; R.I.N.A.; A.B.S. and others are possible. If inspection is required please indicate in your order.

6. Technical data:

temperature ranges
 - calculation temperature (pressure vessel): - 10°C to +100°C
 - medium temperature: - 10°C to +80°C
 - ambient temperature: - 40°C to +60°C
 - survival temperature: - 40°C to +100°C (short-time)
 operating medium: mineral oil, other media on request
 max. operating pressure housing: 40 bar
 test pressure acc. to PED 97/23/EC: 1,43 x operating pressure = 57 bar
 test pressure acc. to ASME VIII Div. 1: 1,3 x operating pressure = 52 bar
 test pressure acc. to API 614, Chapter 1: 1,5 x operating pressure = 60 bar
 connection system: SAE-flange connection 3000 PSI
 housing material: steel
 sealing material: Nitrile (NBR) or Viton (FPM), other materials on request
 installation position: vertical
 bleeder connection : NPT ½" and SAE ¼" 3000 PSI
 drain connection dirt side : NPT ½" and SAE ¼" 3000 PSI
 drain connection clean side : NPT ½" and SAE ¼" 3000 PSI
 volume tank DA 631: 2x 8,3 l
 DA 1001: 2x 11,8 l
 operating pressure adapter flanges: according to B16.5 CLASS 150 PSI / DIN EN 1092-1

Classified under the Pressure Equipment Directive 97/23/EC for mineral oil (fluid group 2), Article 3, Para. 3.
 Classified under ATEX Directive 94/9/EC according to specific application (see questionnaire sheet-no. 34279-4)

7. Symbols:



8. Pressure drop flow curves:

Precise flow rates see 'Interactive Product Specifier', respectively Δp- curves; depending on filter fineness and viscosity.

9. Test methods:

Filter elements are tested according to the following ISO standards:

ISO 2941	Verification of collapse/burst resistance
ISO 2942	Verification of fabrication integrity
ISO 2943	Verification of material compatibility with fluids
ISO 3723	Method for end load test
ISO 3724	Verification of flow fatigue characteristics
ISO 3968	Evaluation of pressure drop versus flow characteristics
ISO 16889	Multi-pass method for evaluating filtration performance