



Big Pleated High Flow Filter Cartridges

Grace Big Pleated High Flow Filter Cartridges utilize pleated depth media and result in exceptional flow capacity, low pressure drop and excellent retention efficiency. The considerate design of top handle makes manual operation quick and easy. Extended service life and less maintenance requirement make the filter cartridges as one of the most cost-saving solutions in big RO applications.

- Ⓞ **High surface area results in longer service life, lower pressure drop and higher flow capacity.**
- Ⓞ **The considerate design of top handle makes change out quick and easy.**
- Ⓞ **Extended service life and less maintenance requirement make the cartridges as one of the most cost-saving solutions.**
- Ⓞ **Available in various sizes and filter media to meet different needs and applications.**
- Ⓞ **Free of additives and binders due to advanced thermally welding construction.**

Applications

Pre RO/DI, Cooling Water, Chemicals, Petrochemical, Electronics, Food & Beverage, Petrochemical

Specifications

Type	Polypropylene Melt Blown	Polypropylene Fiber Pleated	Glass Fiber Pleated	Polyethersulfone Pleated
Micron Rating	1, 5, 10, 20, 30, 50, 100 µm	1, 5, 10, 20, 40, 70 µm	1, 5, 10, 20 µm	0.1, 0.2, 0.5, 1 µm
O-ring	Silicone, EPDM, Viton, Teflon encapsulated Viton			
Core	Glass Filled Polypropylene	Glass Filled Polypropylene	Glass Filled Polypropylene	Glass Filled Polypropylene
Filter Support	Polypropylene	Polypropylene	Polyester	Polypropylene
End Cap	Glass Filled Polypropylene	Glass Filled Polypropylene	Glass Filled Polypropylene	Glass Filled Polypropylene
Cage	Glass Filled Polypropylene	Glass Filled Polypropylene	Glass Filled Polypropylene	Glass Filled Polypropylene
Inside Diameter	3"(75mm)			
Outside Diameter	6"(152mm)			

Operation Data


	Polypropylene	Glass Fiber	Polyethersulfone
Maximum Operating Temperature	82°C (180°F)	121°C (250°F)	82°C (180°F)
Maximum Differential Pressure	3.4 bar at 82°C (50 psi at 180°F), 2.2 bar at 25°C (33 psi at 77°F)		
Recommended Change Out Differential Pressure	2.2 bar (33 psi)		

For more information:

WEB: FLTR.com.au PHONE: (+61) 1300 62 4020 EMAIL: info@FLTR.com.au SKYPE: Purple.Engineering

Big Pleated High Flow Filter Cartridges

40" Polypropylene Big Pleated High Flow Filter Cartridge



Ordering Information

Type	Series	Micron Rating	Filter Media	Nominal Length (inch)	End Cap	O-ring
PB Melt Blown Filter Cartridge	AT - ATO Series	01 – 0.1 μm	P -Polypropylene S -Polyethersulfone G -Glass Fiber	20 - 20" 40 - 40" 60 - 60" Other Customized Sizes	(blank) -Open End N -Sealed End	S -Silicone E -EPDM V -Viton W -Teflon encapsulated Viton
		02 – 0.2 μm				
GD PP Fiber Pleated Filter Cartridge	AT - ATO Series	0H – 0.45 μm	P -Polypropylene S -Polyethersulfone G -Glass Fiber	20 - 20" 40 - 40" 60 - 60" Other Customized Sizes	(blank) -Open End N -Sealed End	S -Silicone E -EPDM V -Viton W -Teflon encapsulated Viton
		1 – 1 μm				
GD PP Fiber Pleated Filter Cartridge	AT - ATO Series	2 – 2 μm	P -Polypropylene	20 - 20"	N -Sealed End	E -EPDM O-ring
		5 – 5 μm				
GD PP Fiber Pleated Filter Cartridge	AT ATO Series	5 5 μm	P Polypropylene	20 20"	N Sealed End	E EPDM O-ring

For more information:

WEB: FLTR.com.au PHONE: (+61) 1300 62 4020 EMAIL: info@FLTR.com.au SKYPE: Purple.Engineering