



TECHNICAL DATA			
FLOW RATE	MAX. 4,000 GPM (908 m ³ /hr)		
SCREEN SIZE	____ MICRON		
SCREEN AREA	12.5 SQ. FEET		
DESIGN TEMPERATURE	160 °F		
DESIGN PRESSURE	150 PSI		
EMPTY WEIGHT	~800 LBS.		
FULL WEIGHT	~1,200 LBS.		

NOTES:
1. PLEASE ALLOW ~20" ADDITIONAL TO INSTALL AND REMOVE THE PISTON ASSEMBLY TO THE BACKSIDE OF THE FILTER.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)			
A1	SERVICE PORT	FLANGED	3.5" ASA	CL. #150 F.F. w/ Blind	FRAC. ±1/16 .X ±.1 .XX ±.05 .XXX ±.010			
A2	PRESSURE RELEASE	THREADED	1" NPT(2)		ANGLE ±1° 			
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)					
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)					
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)	CLASS #150 F.F.S.O.	MATERIAL: SST	TITLE: ABW10-SLP FILTER, CUT DRAWING		
N1	INLET	FLANGED	10" ASA	CLASS #150 F.F.S.O.	DRAWN BY: M. SERRANO			
N2	OUTLET	FLANGED	10" ASA		DATE: 12/19/18			
N3	FLUSH OUTLET	THREADED	2" NPT		SCALE: 1:18	SHEET: 1 OF 1	DRAWING NUMBER ABW-10SLP-CUT-01	REV N/A