



REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL
1	ALL	ADDED SERVICE PORT, CHANGED "WORKING" TO "DESIGN" & TEMPERATURE FROM "200°F" TO "160°F" IN TECHNICAL TABLE, ADDED 2" NPT THREAD TO FLANGES.	01/10/13	S.P.



TECHNICAL DATA

FLOW RATE	MAX. 200 GPM (45 m <sup>3</sup> /hr)
SCREEN SIZE	____ MICRON
SCREEN AREA	1.4 SQ. FEET
DESIGN TEMPERATURE	160 °F
DESIGN PRESSURE	150 PSI
EMPTY WEIGHT	~150 LBS.
FULL WEIGHT	~250 LBS.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)		
A1	SERVICE PORT	THREADED	2" NPT	CLASS #150 F.F.S.O.			FRAC. ±1/16      ANGLE ±1° .X ±.1 .XX ±.05 .XXX ±.010
A2	PRESSURE RELEASE	THREADED	1" NPT(2)				
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)		DRAWN BY: S. PERKINSON	MATERIAL: SST	TITLE: ABW2-SP FILTER WITH 2" NPT SERVICE PORT, CUT DRAWING
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)				
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)		DATE: 09/20/11	DRAWING NUMBER	REV
N1	INLET	FLANGED/THREADED	2" ASA W/ 2" NPT				
N2	OUTLET	FLANGED/THREADED	2" ASA W/ 2" NPT		CLASS #150 F.F.S.O.	SCALE: 1:8	SHEET: 1 OF 1
N3	FLUSH OUTLET	THREADED	2" NPT			ABW-2SP-CUT-01	1