


REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL
1	7D	ADDED NOTE 1.	01/14/15	M.S.
2	4A,54	CHANGED THREADED TO FLANGED UNDER TYPE ON INLET & OUTLET, ADDED RATING TO FLANGES	02/03/15	M.S.



TECHNICAL DATA

FLOW RATE	MAX. 300 GPM (68 m <sup>3</sup> /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	2.5 SQ. FEET
DESIGN TEMPERATURE	160 °F
DESIGN PRESSURE	150 PSI
EMPTY WEIGHT	~225 LBS.
FULL WEIGHT	~425 LBS.

SIDE VIEW

NOTES:  
 1. PLEASE ALLOW ~20" ADDITIONAL TO INSTALL AND REMOVE THE PISTON ASSEMBLY TO THE BACKSIDE OF THE FILTER.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)		
A1	SERVICE PORT	FLANGED	3.5" ASA	CL. #150 F.F. w/ Blind	FRAC. ±1/16	ANGLE ±1°	
A2	PRESSURE RELEASE	THREADED	1" NPT(2)		.X ±.1		
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)		.XX ±.05		<b>MATERIAL:</b> SST
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)		.XXX ±.010		
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)				<b>TITLE:</b> ABW2-XLP FILTER, FLANGED CUT DRAWING
N1	INLET	FLANGED	2" ASA	CLASS #150 F.F.S.O.	<b>DRAWN BY:</b> M. SERRANO		
N2	OUTLET	FLANGED	2" ASA	CLASS #150 F.F.S.O.	<b>DATE:</b> 09/22/14		<b>DRAWING NUMBER</b> ABW-2XLP-CUT-02
N3	FLUSH OUTLET	THREADED	2" NPT		<b>SCALE:</b> 1:10 <b>SHEET:</b> 1 OF 1		