



REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL

TECHNICAL DATA

FLOW RATE	MAX. 200 GPM (45 m <sup>3</sup> /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	1.4 SQ. FEET
WORKING TEMPERATURE	MAX. 200 °F
WORKING PRESSURE	MAX. 150 PSI
EMPTY WEIGHT	~150 LBS.
FULL WEIGHT	#### LBS.

NOZZLE	CONNECTION	TYPE	SIZE	RATING
A1	SERVICE PORT	THREADED	2" NPT	CLASS #150 F.F.S.O. CLASS #150 F.F.S.O.
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)	
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)	
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)	
N1	INLET	FLANGED	3" ASA	
N2	OUTLET	FLANGED	3" ASA	
N3	FLUSH OUTLET	THREADED	2" NPT	

TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
FRAC. $\pm 1/16$	ANGLE $\pm 1^\circ$
.X $\pm .1$	
.XX $\pm .05$	
.XXX $\pm .010$	
<b>MATERIAL:</b> SST	
<b>DRAWN BY:</b> S. PERKINSON	
<b>DATE:</b> 06/14/11	
<b>SCALE:</b> 1:7	
<b>SHEET:</b> 1 OF 1	
<b>TITLE:</b> ABW-3SP FILTER WITH 2" NPT SERVICE PORT, CUT DRAWING	
<b>DRAWING NUMBER</b> ABW-3SP-CUT-02	<b>REV</b> N/A

For more information:

WEB: FLTR.com.au PHONE: (+61) 1300 62 4020 EMAIL: info@FLTR.com.au SKYPE: Purple.Engineering

