



TECHNICAL DATA

Flow Rate	Max. 800 gpm
Screen Size	___ Micron
Screen Area	5.0 sq.ft.
Working Temp.	200 deg. F
Working Pressure	150 PSI
Empty Weight	280 lbs.
Full Weight	590 lbs.

NOZZLE	CONNECTION	TYPE OF CONNECTION	SIZE	RATING
A1	Service Port	Flanged	3.5" ASA	150 lbs. F.F. w/ blind
A2	Pressure Release	Threaded	1" NPT(2)	
K1	Hi. Press. Conn.	Threaded	1/4" NPT(2)	
K2	Low Press. Conn.	Threaded	1/4" NPT(2)	150 lbs. F.F.
K3	Hydraulic Conn.	Threaded	1/4" NPT(2)	
N1	Inlet	Flanged	6" ASA	
N2	Outlet	Flanged	6" ASA	150 lbs. F.F.
N3	Flushoutlet	Threaded	2" NPT	

<small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES DECIMALS ANGULAR .XX + .05 ± 0.5 DEG. .XXX + .01</small>		AUTOMATIC FILTERS, INC. 2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 (310) 839-2828 FAX (310) 839-6878	
		TITLE <h2 style="text-align: center;">ABW6-L</h2>	
DRAWN Daniel Stenberg	DATE 6-20-05	SIZE A	DWG NO. ABW6-L
CHECKED	DESIGN	SCALE 1:11	REV 0 SHEET OF

For more information:

WEB: FLTR.com.au PHONE: (+61) 1300 62 4020 EMAIL: info@FLTR.com.au SKYPE: Purple.Engineering

