


TECHNICAL DATA

FLOW RATE	MAX. 1,500 GPM (341 m ³ /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	16.0 SQ. FT. (2 x 8.0 SQ. FT.)
DESIGN TEMPERATURE	160 °F
DESIGN PRESSURE	150 PSI
EMPTY WEIGHT	~1,100 LBS.
FULL WEIGHT	~2,100 LBS.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)			
A1	SERVICE PORT	FLANGED	3.5" ASA(2)	CL. #150 F.F. w/ Blind	FRAC. ±1/16	ANGLE ±1°		TITLE: ABW6-TXLP FILTER, ONE HOUSING, CUT DRAWING
A2	PRESSURE RELEASE	FLANGED	1" NPT(3)		.X ±.1			
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)		.XX ±.05			
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)		.XXX ±.010			
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)					
N1	INLET	FLANGED	6" ASA	CLASS #150 F.F.S.O.	MATERIAL: SST		DRAWN BY: S. PERKINSON	
N2	OUTLET	FLANGED	6" ASA	CLASS #150 F.F.S.O.	DATE: 10/23/12			
N3	FLUSH OUTLET	FLANGED	3" ASA	CLASS #150 F.F.S.O.	SCALE: 1:17	SHEET: 1 OF 1	DRAWING NUMBER ABW-6TXLP-1HOUS-CUT-01	
							REV	N/A