



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

TECHNICAL DATA

Flow Rate	Max. 800 GPM
Screen Size	--- Micron
Screen Area	5.0 Sq.Ft.
Working Temp.	200 deg. F
Working Pressure	150 PSI
Empty Weight	200 lbs.
Full Weight	---- lbs.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES

DECIMALS	ANGULAR
.XX ± .05	± 0.5 DEG.
.XXX ± .01	

DRAWN	DATE
Daniel Stenberg	2-17-06
CHECKED	
DESIGN	



CSB6-L

NOZZLE	CONNECTION	TYPE OF CONNECTION	SIZE	RATING
K1	Hi. Press. Conn.	Threaded	1/4" NPT(2)	
K2	Low Press. Conn.	Threaded	1/4" NPT(2)	
K3	Flushoutlet Conn.	Threaded	1/4" NPT(2)	
N1	Inlet	Flanged	6" ASA	150 lbs. F.F.
N2	Outlet	Flanged	6" ASA	150 lbs. F.F.
N3	Flushoutlet	Threaded	2" NPT	

SIZE	DWG NO.	REV
A	CSB6-L	0
scale 1:14		SHEET OF