


| REVISIONS | | | | |
|-----------|-----|-------------|------|----------|
| ZONE | REV | DESCRIPTION | DATE | APPROVED |
| | | | | |

TECHNICAL DATA

| | |
|------------------|---------------|
| Flow Rate | Max. 1500 GPM |
| Screen Size | _____ Micron |
| Screen Area | 7.0 sq.ft |
| Working Temp. | 200 deg. F |
| Working Pressure | 150 PSI |
| Empty Weight | 380 lbs. |
| Full Weight | _____ lbs. |

| NOZZLE | CONNECTION | TYPE OF CONNECTION | SIZE | RATING |
|--------|------------------|--------------------|--------------|---------------|
| K1 | Hi. Press. Conn. | Threaded | 1/4" NPT (2) | 150 lbs. F.F. |
| K2 | Low Press. Conn. | Threaded | 1/4" NPT (2) | |
| K3 | Hydraulic Conn. | Threaded | 1/4" NPT (2) | |
| N1 | Inlet | Flanged | 6" ASA | |
| N2 | Outlet | Flanged | 6" ASA | |
| N3 | Flushoutlet | Threaded | 2" NPT | 150 lbs. F.F. |

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES
DECIMALS ANGULAR
.XX ± .05 ± 0.5 DEG.
.XXX ± .01



FLTR
Purple Engineering

| | | | |
|--------------|----------|------|--------------|
| TITLE | | | |
| CSB6-S | | | |
| DRAWN | DATE | | |
| S. Perkinson | 10/18/10 | | |
| CHECKED | | SIZE | DWG NO. |
| | | A | CSB6-S |
| DESIGN | | | REV |
| | | | N/A |
| NOT TO SCALE | | | SHEET 1 OF 1 |