




REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL
1	7D	ADDED NOTE 1.	04/16/15	M.S.

TECHNICAL DATA

FLOW RATE	MAX. 600 GPM (136 m ³ /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	2.5 SQ. FEET
DESIGN TEMPERATURE	160 °F
DESIGN PRESSURE	150 PSI
EMPTY WEIGHT	~260 LBS.
FULL WEIGHT	~460 LBS.

NOTES:
 1. PLEASE ALLOW ~20" ADDITIONAL TO INSTALL AND REMOVE THE PISTON ASSEMBLY TO THE BACKSIDE OF THE FILTER.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)		
A1	SERVICE PORT	FLANGED	3.5" ASA	CL. #150 F.F. w/ Blind	FRAC. ±1/16	ANGLE ±1°	
A2	PRESSURE RELEASE	THREADED	1" NPT(2)		.X ±.1		
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)		.XX ±.05		DRAWING NUMBER: LPF-6P-CUT-01 REV: 1
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)		.XXX ±.010		
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)		MATERIAL: SST		DATE: 04/11/12 SCALE: 1:10 SHEET: 1 OF 1
N1	INLET	FLANGED	6" ASA	CLASS #150 F.F.S.O.	DRAWN BY: S. PERKINSON		
N2	OUTLET	FLANGED	6" ASA	CLASS #150 F.F.S.O.			
N3	FLUSH OUTLET	THREADED	2" NPT				