

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

TECHNICAL DATA


Flow Rate Max. 6000 GPM
 Screen Size ----- Micron
 Screen Area 16.5 sq.ft (Perf.)
 Working Temp. 200 deg. F
 Working Pressure 150 PSI
 Empty Weight --- lbs.
 Full Weight ----- lbs.

NOZZLE	CONNECTION	TYPE OF CONNECTION	SIZE	RATING
K1	Hi. Press. Conn.	Threaded	1/4" NPT(2)	150 lbs. F.F. 150 lbs. F.F.
K2	Low Press. Conn.	Threaded	1/4" NPT (2)	
K3	Hydraulic Conn.	Threaded	1/4" NPT(2)	
N1	Inlet	Flanged	16" ASA	
N2	Outlet	Flanged	16" ASA	
N3	Flushoutlet	Threaded	2" NPT	

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES
 TOLERANCES

DECIMALS	ANGULAR
XX ± .05	± 0.5 DEG
XXX ± .01	

DRAWN	DATE
Daniel Stenberg	4-10-06
CHECKED	
DESIGN	



FLTR
Purple Engineering

TITLE
CSB 16-L
Coarse Screen Brush
Filter

SIZE	DWG NO.	REV
A	CSB16-L	0

NOT SCALE SHEET OF