



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

TECHNICAL DATA

Flow Rate	Max. 20,000 GPM
Screen Size	___ Micron
Screen Area	48.0 sq.ft (Perf.)
Working Temp.	200 deg. F
Working Pressure	150 PSI
Empty Weight	___ lbs.
Full Weight	___ lbs.

NOZZLE	CONNECTION	TYPE OF CONNECTION	SIZE	RATING
K1	Hi. Press. Conn.	Threaded	1/4" NPT(2)	
K2	Low Press. Conn.	Threaded	1/4" NPT (2)	
K3	Hydraulic Conn.	Threaded	1/4" NPT(2)	
N1	Inlet	Flanged	24" ASA	150 lbs. F.F.
N2	Outlet	Flanged	24" ASA	150 lbs. F.F.
N3	Flushoutlet	Threaded	2" NPT	

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES
DECIMALS ANGULAR
XX ± .05 ± 0.3 DEG
XXX ± .01



TITLE			
CSB 24-TS Coarse Screen Brush Filter			
DRAWN	DATE	SIZE	DWG NO.
Daniel Stenberg	2-27-06	A	CSB24-TS
CHECKED		REV	
		0	
DESIGN		NOT TO SCALE	SHEET OF